

Team Biland AG

Revolutions per minute 13'000 1/min Circumference of wheel 885 mm

Sprocket	Pinion	Transmission	Diff.	Km/h
70	15	4.67	2.08	147.92
71	15	4.73	2.03	145.84
72	15	4.80	1.97	143.81
73	15	4.87	1.92	141.84
74	15	4.93	1.87	139.93
75	15	5.00	1.82	138.06
76	15	5.07	1.77	136.24
77	15	5.13	1.72	134.47
78	15	5.20	1.68	132.75
79	15	5.27	1.64	131.07
80	15	5.33	1.23	129.43
70	13	5.38	0.37	128.20
81	15	5.40	1.44	127.83
71	13	5.46	0.12	126.39
82	15	5.47	1.52	126.27
83	15	5.53	0.12	124.75
72	13	5.54	1.37	124.64
84	15	5.60	0.34	123.27
73	13	5.62	1.11	122.93
85	15	5.67	0.55	121.82
74	13	5.69	0.87	121.27
86	15	5.73	0.75	120.40
75	13	5.77	0.63	119.65
87	15	5.80	0.94	119.02
76	13	5.85	0.41	118.08
88	15	5.87	1.12	117.66
77	13	5.92	0.20	116.54
89	15	5.93	1.29	116.34
78	13	6.00	0.00	115.05
90	15	6.00	1.26	115.05
91	15	6.07	0.19	113.79
79	13	6.08	1.04	113.59
92	15	6.13	0.38	112.55
80	13	6.15	1.38	112.17
81	13	6.23	1.35	110.79

Sprocket	Pinion	Transmission	Diff.	Km/h
82	13	6.31	0.96	109.44
70	11	6.36	0.36	108.48
83	13	6.38	1.17	108.12
71	11	6.45	0.12	106.95
84	13	6.46	1.26	106.83
85	13	6.54	0.11	105.58
72	11	6.55	1.11	105.46
86	13	6.62	0.33	104.35
73	11	6.64	0.87	104.02
87	13	6.69	0.54	103.15
74	11	6.73	0.64	102.61
88	13	6.77	0.73	101.98
75	11	6.82	0.41	101.24
89	13	6.85	0.92	100.83
76	11	6.91	0.20	99.91
90	13	6.92	1.10	99.71
77	11	7.00	0.00	98.61
91	13	7.00	1.07	98.61
92	13	7.08	0.19	97.54
78	11	7.09	1.23	97.35
79	11	7.18	1.20	96.12
80	11	7.27	1.17	94.92
81	11	7.36	1.14	93.74
82	11	7.45	1.12	92.60
83	11	7.55	1.09	91.49
84	11	7.64	1.06	90.40
85	11	7.73	1.04	89.33
86	11	7.82	1.01	88.29
87	11	7.91	0.99	87.28
88	11	8.00	0.97	86.29
89	11	8.09	0.95	85.32
90	11	8.18	0.93	84.37
91	11	8.27	0.91	83.44
92	11	8.36		82.54